

ARTICULATED BOOMS | AJ48D



PLATFORM HEIGHT
48' 3" / 14.7m

PLATFORM CAPACITY
551lbs / 250kg

PLATFORM REACH
27' 4" / 8.3m

HIGHER STANDARDS OF DESIGN.

User friendly control panel and joystick layout coupled with function speed control, provides smooth, stable operation.



SAFE & SECURE

Auxiliary handrail provides enhanced protection against crush injuries to the operator.



HIGHER STANDARDS OF MANUFACTURE.

We've developed a highly durable and robust structure, integrated with a Bosch Electronic Control System and proven components from our construction equipment.



EFFICIENCY BUILT IN

Colour base display provides the highest level of machine feedback, including platform load and diagnostics.

HIGHER STANDARDS OF TOUGHNESS.

We've treated the platform to give the highest level of EPD protection, providing an extremely durable, rust-resistant finish for years to come.



BUILT TO LAST

Electrical components are rated to IP67, enabling work in the toughest of rental environments.



HIGHER STANDARDS OF BACK-UP.

With trained engineers and technicians across 2,200 dealer depots globally, JCB can deliver the back-up that the powered access market has been waiting for.



PEACE OF MIND

JCB engineers are trained and authorised to complete all routine servicing and breakdown repairs, including the JCB by Kohler engine.

HIGHER STANDARDS OF TELEMATICS.

Fitted as standard, JCB LiveLink provides maximum machine uptime by sending notifications on machine performance, utilisation and health alerts.



FITTED AS STANDARD



BEST-IN-CLASS
48ft platform height provides the greatest working envelope in it's size class.



ARTICULATED BOOMS | AJ48D



SPECIFICATION.

MODEL	AJ48D
Platform Height	48ft 4in / 14.7m
Maximum Reach	27ft 4in / 8.3m
Up and Over Clearance	24ft 4in / 7.5m
Stowed Length	24ft 1in / 7.35m
Width	7ft 5in / 2.26m
Platform Capacity	551lbs / 250kg
Weight	17,383lbs / 7,885kg



STANDARD FEATURES.

- JCB by Kohler engine 47HP (35 kW)
- 7" touchscreen display
- Platform tool tray
- Secondary Guarding
- Full height entry gate
- Solid rough terrain tyres
- Pull-out engine tray
- 4-wheel drive
- 250hr boom greasing interval
- 5yr JCB LiveLink as standard



Choose JCB's AJ48D Articulated Boom

FIND A DEALER

FIND OUT MORE



www.jcb.com

